






















| Обозначение | Температура обжига | Цвет | Для напыления | Сухая просыпка | Примечание |
|-------------|--------------------|---|---------------|----------------|------------|
| S 400/291 | 980-1080°C | коричневый  | • | • | |
| S 400/292 | 980-1080°C | кремовый  | • | • | |
| S 400/293 | 980-1080°C | зеленый  | • | • | |
| S 400/398 | 980-1080°C | желтый ochre  | • | • | |
| S 400/400 | 980-1080°C | желтый  | • | • | |
| S 400/445 | 980-1080°C | коричневый  | • | • | |
| S 400/446 | 980-1080°C | желтый-коричневый  | • | • | |
| S 400/448 | 980-1080°C | "ivory" белый  | • | • | |
| S 400/449 | 980-1080°C | "avana"  | • | • | |
| S 400/450 | 980-1080°C | зеленый  | • | • | |
| S 400/459 | 980-1080°C | кремовый  | • | • | |
| S 400/472 | 980-1080°C | желтый  | • | • | |
| S 400/473 | 980-1080°C | оранжевый  | • | • | |
| S 400/479 | 980-1080°C | фиолетовый  | • | • | |
| S 400/482 | 980-1080°C | красный  | • | • | |
| S 400/489 | 980-1080°C | темно-коричневый  | • | • | |
| S 400/548 | 980-1080°C | зеленый  | • | • | |
| S 400/547 | 980-1080°C | зеленый  | • | • | |

| Обозначение | Температура обжига | Цвет | Для напыления | Сухая просыпка | | Примечание |
|-------------|--------------------|---|---------------|----------------|--|------------|
| S 400/545 | 980-1080°C | желтый  | • | • | | |
| S 400/546 | 980-1080°C | красный  | • | • | | |
| S 400/517 | 980-1080°C | оранжевый  | • | • | | |